## Get more with interlock

GM-4CS

STAND ALONE

### GAS MINDER WITH BUILT-IN DUAL **FAN CURRENT SENSOR GM-4CS**





#### ISP-3 System pack comprises of: 1x GM-4 control unit 1x DPSA-20 pressure switch 1x DK-1 duct kit 1x EM-1 remote emergency stop button JUST NOTE: All above to be used with 230 Vac ZEV gas solenoid valves. Mandatory requirement for commercial kitchens which meets BS 6173:2009.



# GM-4

#### STAND ALONE GAS MINDER

GM-4	Control unit complies with all current Corgi gas	
	regulations for commercial kitchens. IP56 rated	
	control box ensures there is no gas flow to burners	
	unless air extraction is present.	£160.00

P30





P30	For 3 zone gas detection - Control Unit	£244.00
S71	Natural Light gas - Sensor for above	£107.00
S72	LPG - Sensor for above	£107.00

#### ISP-4

System pack comprises of:

1x GM-4 control unit

1x CS-2 Dual fan current sensor

1x EM-1 remote emergency stop button

NOTE: All above to be used with 230 Vac ZEV gas solenoid valves.

Mandatory requirement for commercial kitchens which meets BS 6173:2009.





#### **FAN CURRENT SENSOR TO INTERLOCK UP TO TWO FANS**

CS-2	Dual fan current sensor is designed to be used to	
	interlock two fans as an alternative method of	
	interlocking to differential air pressure switches.	£130.00



#### STAND ALONE GAS DETECTORS

Visual and audible alarm with volt free relay output, sensor failure indication, mute button.

PII	Natural , Light gas	£132.00
P12	LPG	£132.00
P13	Carbon Monoxide	£255.00