

SOLENOID COILS AND CONECTORS FOR VALVE BODIES



HOMOLOGATION AND STANDARDS

- > Complies with EN 60335-1 standards
- > CE: C102410

NOTE

When used at 60 Hz, the pressure valves indicated in the valve body tables should be reduced by approx 12%.
With DC voltage coils, the pressure values indicated in the valve body tables should be reduced by approx 60%.

TECHNICAL FEATURES

- > All coils are produced with copper wire in H class (180°C)
- > 30% glass fibre thermoplastic body, insulation class F (155 suitable for continuous duty (100% ED))
- > IP65 protection degree
- > Voltage tolerance: +10% in AC and +10-5 % in DC
- > Electrical connector over 2P+ DIN 43650 socket

COILS SUITABLE FOR SOLENOID VALVES

TYPE	Power Supply	Starting Power	Starting Power	Max Working Temp
		VA	W	°C
C12DC	12 Vdc	-	12	80
C24DC	24 Vdc	-	12	80
C24AC	24 Vac	25	14	80
C110	110 Vac	25	9	80
C230	230 Vac	25	14	80



TECHNICAL FEATURES

- > Push-on connector in compliance with DIN 43650, suitable for all coils.
- > Cable gland (Cable diameter 6 to 8mm)

PRODUCT INFORMATION

TYPE	Description
1578501	Rotational connector DIN 43650 Form A

SPARE DIAPHRAGMS | D-SPARES



D-SPARES

Spare diaphragms for servo-assisted valves 23 & 29 series. EPDM.

- D-10/15 Valve size 3/8" and 1/2" series 23 and 29
- D-20/25 Valve size 3/4" and 1" series 23 and 29
- D-32/40 Valve size 1 1/4" and 1 1/2" series 23 and 29
- D-50 Valve size 2" series 23 and 29

Need Some Help? GET IN CONTACT:

+44 (0)161 946 0088
banicocontrols.com
info@banico.co.uk

