

AUTOMATIC VALVES - ALTERNATIVE VOLTAGE | ZEV

Gas Solenoid Valves are used for the safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural gas, Propane and LPG. With 1/4" inlet and outlet plugs, suitable for CPI switch, pressure gauge. Suitable for use with gas pressure proving and interlock systems.



Available with LED Indicator

SUPPLY VOLTAGE 24VAC (-15% +10%) 50-60 HZ

TYPE	SIZE	CONNECTION	MAX PRESSURE	SUPPLY (-15% +10%)	POWER (W)	WEIGHT (Kgs)
ZEV10-24	3/8"	BSP	360 mbar	24 Vac	25	1.10
ZEV15-24	1/2"	BSP	360 mbar	24 Vac	25	1.10
ZEV20-24	3/4"	BSP	360 mbar	24 Vac	25	2.20
ZEV25-24	1"	BSP	360 mbar	24 Vac	25	2.20
ZEV32-24	1 1/4"	BSP	360 mbar	24 Vac	55	5.00
ZEV40-24	1 1/2"	BSP	360 mbar	24 Vac	55	5.00
ZEV49-24	2"	BSP	360 mbar	24 Vac	55	5.20
ZEV50-24	2"	BSP	360 mbar	24 Vac	55	6.20
ZEV65-24	2 1/2"	BSP	360 mbar	24 Vac	90	12.90
ZEV80-24	3"	BSP	360 mbar	24 Vac	90	12.80
ZEVF65-24	65mm (2 1/2")	Flanged PN16	360 mbar	24 Vac	90	15.00
ZEVF80-24	80mm (3")	Flanged PN16	360 mbar	24 Vac	90	15.30



Available with IP65



ZEV20-24



Available with LED Indicator

SUPPLY VOLTAGE 110VAC (-15% +10%) 50-60 HZ

TYPE	SIZE	CONNECTION	MAX PRESSURE	SUPPLY (-15% +10%)	POWER (W)	WEIGHT (Kgs)
ZEV10-110	3/8"	BSP	360 mbar	110 Vac	15	1.10
ZEV15-110	1/2"	BSP	360 mbar	110 Vac	15	1.10
ZEV20-110	3/4"	BSP	360 mbar	110 Vac	25	2.20
ZEV25-110	1"	BSP	360 mbar	110 Vac	25	2.20
ZEV32-110	1 1/4"	BSP	360 mbar	110 Vac	45	5.00
ZEV40-110	1 1/2"	BSP	360 mbar	110 Vac	45	5.00
ZEV49-110	2"	BSP	360 mbar	110 Vac	45	5.20
ZEV50-110	2"	BSP	360 mbar	110 Vac	45	6.20
ZEV65-110	2 1/2"	BSP	360 mbar	110 Vac	86	12.90
ZEV80-110	3"	BSP	360 mbar	110 Vac	86	12.80
ZEVF65-110	65mm (2 1/2")	Flanged PN16	360 mbar	110 Vac	86	15.00
ZEVF80-110	80mm (3")	Flanged PN16	360 mbar	110 Vac	86	15.30



Available with IP65



ZEV20-110

Drop us an email to request our accessories pages info@banico.co.uk



THERMAL LINK



CLOSED POSITION INDICATION SWITCH

In addition to the standard controls featured, we can also supply customised products, designed and manufactured to meet your exact needs. If you need the controls badged, no problem, let us know your particular marketing requirements.



Need Some Help? GET IN CONTACT:

0161 946 0088

banico.co.uk
info@banico.co.uk

AUTOMATIC VALVES - ALTERNATIVE VOLTAGE | ZEV

Gas Solenoid Valves are used for the safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural gas, Propane and LPG. With 1/4" inlet and outlet plugs, suitable for CPI switch, pressure gauge. Suitable for use with gas pressure proving and interlock systems.

SUPPLY VOLTAGE 24VDC AUTOMATIC ON/OFF

TYPE	SIZE	CONNECTION	MAX PRESSURE	SUPPLY (-15% + 10%)	POWER (W)	WEIGHT (Kgs)
ZEV10-24DC	3/8"	BSP	360	24 Vdc	12	1.10
ZEV15-24DC	1/2"	BSP	360	24 Vdc	12	1.10
ZEV20-24DC	3/4"	BSP	360	24 Vdc	20	2.20
ZEV25-24DC	1"	BSP	360	24 Vdc	20	2.20
ZEV32-24DC	1 1/4"	BSP	360	24 Vdc	35	5.00
ZEV40-24DC	1 1/2"	BSP	360	24 Vdc	35	5.00
ZEV49-24DC	2"	BSP	360	24 Vdc	35	5.20
ZEV50-24DC	2"	BSP	360	24 Vdc	35	6.20
ZEV65-24DC	2 1/2"	BSP	360	24 Vdc	65	12.90
ZEV80-24DC	3"	BSP	360	24 Vdc	65	12.80
ZEVF65-24DC	65mm (2 1/2")	Flanged PN16	360	24 Vdc	65	15.00
ZEVF80-24DC	80mm (3")	Flanged PN16	360	24 Vdc	65	15.30
ZEVF100-24DC	100mm (4")	Flanged PN16	360	24 Vdc	65	36



Available with LED Indicator



Available with IP65



ZEV20-24DC

SUPPLY VOLTAGE 12VDC AUTOMATIC ON/OFF

TYPE	SIZE	CONNECTION	MAX PRESSURE	SUPPLY (-15% + 10%)	POWER (W)	WEIGHT (Kgs)
ZEV10-12DC	3/8"	BSP	360 mbar	12 Vdc	12	1.10
ZEV15-12DC	1/2"	BSP	360 mbar	12 Vdc	12	1.10
ZEV20-12DC	3/4"	BSP	360 mbar	12 Vdc	20	2.20
ZEV25-12DC	1"	BSP	360 mbar	12 Vdc	20	2.20
ZEV32-12DC	1 1/4"	BSP	360 mbar	12 Vdc	35	5.00
ZEV40-12DC	1 1/2"	BSP	360 mbar	12 Vdc	35	5.00
ZEV49-12DC	2"	BSP	360 mbar	12 Vdc	35	5.20
ZEV50-12DC	2"	BSP	360 mbar	12 Vdc	35	6.20
ZEV65-12DC	2 1/2"	BSP	360 mbar	12 Vdc	65	12.90
ZEV80-12DC	3"	BSP	360 mbar	12 Vdc	65	12.80
ZEVF65-12DC	65mm (2 1/2")	Flanged PN16	360 mbar	12 Vdc	65	15.00
ZEVF80-12DC	80mm (3")	Flanged PN16	360 mbar	12 Vdc	65	15.30



Available with LED Indicator



Available with IP65



ZEV20-12DC

Drop us an email to request our accessories pages info@banico.co.uk



THERMAL LINK



CLOSED POSITION INDICATION SWITCH

In addition to the standard controls featured, we can also supply customised products, designed and manufactured to meet your exact needs. If you need the controls badged, no problem, let us know your particular marketing requirements.



Need Some Help? GET IN CONTACT:

0161 946 0088

banico.co.uk
info@banico.co.uk