

## SPARES & ACCESSORIES

Spare parts and accessories that can be used in conjunction with valves and controls within our range.

### SPARE COILS ZEV RANGE

C-ZEV10/15	For 3/8" and 1/2"
C-ZEV20/25	For 3/4" and 1"
C-ZEV32/40	For 1 1/4" and 1 1/2"
C-ZEV50	For 2"
C-ZEV65/80	For 2 1/2", 3", 65mm and 80mm
C-ZEVF100	For 100mm
C-ZEVF125/150/200	For 125mm, 150mm and 200mm

Please specify voltage when ordering




C-ZEV20/25

### SPARE TERMINAL BOX INCLUDING ELECTRONIC BOARD

TB-10/15	Valve size 3/8" and 1/2"
TB-20/25	Valve size 3/4" and 1"
TB-32/40	Valve size 1 1/4" and 1 1/2"
TB-50	Valve size 2"
TB-65/80	Valve size 2 1/2" and 3" BSP and Flanged
TB-100	Valve size 4" Flanged
TB-125/150/200	Valve size 5", 6" and 8" Flanged

Please specify voltage when ordering



TB-10/15

### CLOSED POSITION INDICATION SWITCH

The closed position switch can be used on ZEV gas solenoid valves to indicate position of valve.

**Operational Voltage:** 250 Vac 3A, micro switch

**Enclosure:** IP65

**Ambient Temperature:** -15 to +60°C

CPI-10/15	Valve size 3/8" and 1/2"
CPI-20/25	Valve size 3/4" and 1"
CPI-32/40	Valve size 1 1/4" and 1 1/2"
CPI-50	Valve size 2"
CPI-65/80	Valve size 2 1/2" and 3" BSP
CPI-F65/F80	Valve size 65mm and 80mm Flanged
CPI-100	Valve size 4" Flanged
CPI-125/150/200	Valve size 5", 6" and 8" Flanged



CPI-100

Find everything about how to install and maintain our valves on the website.

[banico.co.uk/instruction-sheets](http://banico.co.uk/instruction-sheets)



## SPARES & ACCESSORIES

Spare parts and accessories that can be used in conjunction with vales and controls within our range.

British design.  
British quality.

### THERMAL LINK

The electro fusible thermal link is designed to be used where there is a potential fire hazard such as in a boiler or plant rooms.

In the event of fire the temperature sensitive fuse will interrupt the power supply, activating alarms or shut down devices.

The unit should be mounted so that the perforated cover faces downwards and the ventilation holes in the back/side of the box must not be obstructed.

The link is electrically rated at 5 amps max on 200/250 Vac and melts at 68°C. IP30 Protection.



TL-2

<b>TL-2</b>	Zinc plated steel with a 20mm conduit entry	75x53x31mm
-------------	---	------------

### EMERGENCY STOP BUTTON

The emergency stop button is designed for manual shut down of systems or machines in the event of fire or other emergencies.

Key reset version can be used to prevent any unauthorised restarting of machinery/ system following an emergency shut down.

10 (6) Amps at 230 Vac Volts free contact. IP65 Protection.



EM-1K



EM-1

<b>EM-1</b>	Push to break circuit - Turn to reset
<b>EM-1K</b>	Push to break circuit - Use key to reset

### DIFFERENTIAL PRESSURE SWITCH-AIR

24V-250Vac, 1/5 (0.4)A, Ambient Temp -20°C to 85°C

6mm push on connection, IP54



DK-1



DPSA-20

<b>DPSA-20</b>	0.2-2 mbar (20-200pa)	0.1 mbar diff (10pa)
<b>DPSA-50</b>	0.5-5 mbar (50-500pa)	0.2 mbar diff (20pa)
<b>DK-1</b>	Duct kit, tube plus Connectors	

Technical data and installation instructions are available for most products in other languages.



Need Some Help? GET IN CONTACT:

**0161 946 0088**

[banico.co.uk](http://banico.co.uk)  
[info@banico.co.uk](mailto:info@banico.co.uk)