

Pressure Switches

Water/Steam/Air/Oil



- Adjustable differential
- Cover in shock-proof self-extinguishing thermoplastic
- Metallic frame
- Switch contact rating: 250V 10A (8)
- Switch: SPDT
- Protection: IP40
- Mounting bracket: Included
- PVC grommet for cable entry

Type	Range bar	Differential bar	Max Bellows pressure bar	Connection	protection	Weight Kgs
PS12CF	-0.5 to 6	0.6 to 4	16.5	1/4" BSP female	IP40	0.30
PS12CM	-0.5 to 6	0.6 to 4	16.5	1/4" BSP male	IP40	0.30
PS12DF	5 to 16	2 to 5	33	1/4" BSP female	IP40	0.30

Differential Pressure Switch

Water



- Adjustable differential
- Cover in shock-proof self-extinguishing thermoplastic
- Metallic frame
- Switch contact rating: 250V 10A (8)
- Switch: SPDT
- Protection: IP40
- Mounting bracket: Included
- PVC grommet for cable entry

Type	Range bar	Differential bar	Max working pressure bar	Connection	Protection	Weight Kgs
DPS113-5	0.5 to 4	0.1	30	1/4" BSP female	IP42	0.36
DPS113-2	0.2 to 4	0.1	30	1/4" BSP female	IP42	0.36



Banico Controls
 Tilson Road, Manchester M23 9GF
 Tel: 0161 946 0088 Fax: 08451 700750
 e-mail: info@banico.co.uk www.banico.co.uk

