

11 flow controls

AIR FLOW, HEAVY DUTY WITH STEEL COVER

Adjustable sensitivity, test switch, weatherproof to IP54 SPDT switch

FSA-1	Connection plate		IP45
-------	------------------	--	------

WATER FLOW, HEAVY DUTY WITH STEEL COVER

Adjustable sensitivity 1" BSP brass connection, test switch

FSL-1	1" to 6" pipe	Stainless Steel Paddles	IP45
-------	---------------	-------------------------	------

WATER FLOW, IN LINE

Adjustable sensitivity, test switch

FSP15	½" BSP	Brass body	IP45
FSP20	¾" BSP	Brass body	IP45



differential pressure switch

AIR

24V-250Vac 1.5(0.4)A, Ambient temp -20 to 85°C, 6mm push on connection, IP54

DPSA-20	0.2 - 2 mbar (20-200pa)	0.1 mbar diff (10pa)
DPSA-50	0.5 - 5 mbar (50-500pa)	0.2 mbar diff (20pa)
DK-1	Duct kit, tube + Connectors	



room thermostat

2-wire connection, Vapour pressure sensing

RS-1	5 to 30°C	0.5K diff	6A (3) SPDT
------	-----------	-----------	-------------

Suitable for combination boilers

