

## Strap on thermostat for pipes and cylinders



### TPS-1

- To control water temperature in heating pipe installation
- Liquid expansion operation
- Sensitive element with stainless steel diaphragm
- Base, cover and knob in shock-proof self-extinguishing thermoplastic
- Switch contact rating: 250V 16A (4)
- Range: 0°C to 90°C
- Differential: 6°C
- Protection: IP40
- Fixing strap for pipe and cylinder included

## Strap on thermostat for pipes and cylinders



### TPS-1C

#### tamper proof with concealed knob

- To control water temperature in heating pipe installation
- Liquid expansion operation
- Sensitive element with stainless steel diaphragm
- Base, cover and knob in shock-proof self-extinguishing thermoplastic
- Switch contact rating: 250V 16A (4)
- Range: 0°C to 90°C
- Differential: 6°C
- Protection: IP40
- Fixing strap for pipe and cylinder included

## Capillary thermostat



### TCS-1

- Wall mounting of thermostat body
- Liquid expansion operation
- Sensitive element with stainless steel diaphragm
- Copper bulb and capillary
- Base, cover and knob in shock-proof self-extinguishing thermoplastic
- Switch contact rating: 250V 16A (4)
- Range: 0°C to 90°C
- Differential: 5°C
- Protection: IP40
- Capillary length 1m, sensor element 6.5 x 72mm



Banico Controls  
Tilson Road, Manchester M23 9GF  
Tel: 0161 946 0088 Fax: 08451 700750  
info@banico.co.uk www.banico.co.uk

